

DART SENSORS

Platinum Wire, 99.99%

WIRE CHARACTERISTICS

Size	Tolerance \pm	Specification
0.15mm	0.02mm	99.99%
0.20mm	0.02mm	99.99%
0.25mm	0.02mm	99.99%

IMPURITIES PER KG SALT

Element	Unit	Specification	Element	Unit	Specification
Au	ppm	<50	Cu	ppm	<40
Ag	ppm	<30	Fe	ppm	<50
Pd	ppm	<50	Mg	ppm	<30
Ir	ppm	<50	Mn	ppm	<10
Ru	ppm	<20	Mo	ppm	<40
Rh	ppm	<50	Ni	ppm	<10
Al	ppm	<40	Pb	ppm	<10
As	ppm	<20	Sb	ppm	<20
Bi	ppm	<20	Si	ppm	<50
Ca	ppm	<30	Sn	ppm	<20
Cd	ppm	<50	Te	ppm	<40
Cr	ppm	<10	Zn	ppm	<20

Total: <100 ppm

ORDERING INFORMATION

Part Number	Description
3-W015	1m Pt wire, 0.15 mm dia, 99.99%, annealed, ON SPOOL
3-W020	1m Pt wire, 0.20 mm dia, 99.99%, annealed, ON SPOOL
3-W025	1m Pt wire, 0.25 mm dia, 99.99%, annealed, ON SPOOL



ELM HOUSE, 54 MARY ARCHES STREET, EXETER, EX4 3BA
TEL: +44 (0)1392 277733
E-MAIL: customer.service@dart-sensors.com
www.dart-sensors.com

Revised: 21st December 2020